

# Product Summary

Our Orange Catch Basin Sack is a bright orange porous fabric bag that is fabricated with reinforcing, lifting, support and dumping webbing. The product is positioned between the catch basin and the grate when installed. CB Sacks are available in various sizes depending on the grate to be protected.

#### **Contact Details**

bmpsupplies.com sales@bmpsupplies.com 1.855.422.0066

### **CATCH BASIN SACK**

#### SPECIFICATION SHEET


Body Fabric	Orange PE Mesh Medium Flow Fabric
Tensile Strength	ASTM-D-4632: MD - 336 lbs / TD - 123 LBS
Permeability	ASTM-D-4491: 0.38 cm/s
Grate Size	24" x 24" and 24" x 36" (custom sizes available)
Grab Tensile	ASTM-D-4632 - 115 lb
Compressed Size	8" x 8" x 4"
Expanded Size	Varies depending on Part Number
Permittivity	5.72 (s-1)
Water Flow Rate	428 gal/min/ft²
Optional	Oil Absorbent Pillow for hydrocarbons

The information contained herein is furnished without charge or obligation and the recipient assumes all responsibility for its use. Because conditions of use and handling may vary and are beyond our control, we make no representation about, and are not responsible or liable for the accuracy and reliability of said information or the performance of any product. Any specification, property or application listed herein are provided as information only and in no way modify, amend, enlarge or create any warranty. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.



## **CATCH BASIN SACK**

#### PRODUCT DIAGRAM



The information contained herein is furnished without charge or obligation and the recipient assumes all responsibility for its use. Because conditions of use and handling may vary and are beyond our control, we make no representation about, and are not responsible or liable for the accuracy and reliability of said information or the performance of any product. Any specification, property or application listed herein are provided as information only and in no way modify, amend, enlarge or create any warranty. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.